

Version	2
Date	10/08/2022
N°	GARA-0020

WARRANTY CERTIFICATE

DURASID® FORESTA

For the products in the product range of **DURASID® FORESTA** with the colour **001 (woodland oak), 002 (red cedar), 003 (african padauk), 004 (siberian larch), 005 (barnwood grey), 006 (sheffield oak), 007 (grey cedar) and 008 (woodland grey)** we can guarantee, based on the available information from our suppliers, that the product will not degrade excessive visually under normal use⁽¹⁾. If extraordinary wear occurs in these products within the specified warranty period and under the conditions below, Plastivan will replace the damaged product or refund it, taking into account a depreciation in relation to the already elapsed time and warranty period. Costs for replacement and removal, labour or other costs (e.g. transportation) are not covered by this warranty. Any defect must be passed to Plastivan no later than 2 months after detection.

THIS WARRANTY IS VALID FOR A PERIOD OF 10 YEAR AFTER INSTALLATION

This warranty is valid, taking into account the following conditions:

- Not exposed to temperatures > 40°C
- Installation in conformity with the installation guide, published by Plastivan.
- Damage by use⁽¹⁾ and vandalism are not covered by this warranty.
- Damage by poor storage⁽²⁾ is not covered by this warranty.
- Allow inspections by Plastivan if any abnormality occurs.
- Installation in the EU, Russia, Norway, Moldova, Belarus, with the exception of areas where the UV radiation is higher than 120.000Lys/year (e.g. Southern Europe).



Plastivan nv
Wantestraat 3
8780 Oostrozebeke
Belgium

(1) Use: the materials are treated during their lifespan under the principle of due Diligence.

(2) In good storage means: the materials are stored under the principle of due diligence, in which is taken into account, but not limited to: Saving the goods in their packaging and in an environment with a normal temperatures (max 40 °C) and humidity (RH 70-85%). Storing the goods in an environment that is protected from rain and other weather conditions. It is expected that the panels are not stored for longer than 6 months.